



**NOTES (APPLICABLE 1/P-1):**

- 1 REPLACE EXISTING TOILET CONNECTION WITH NEW FLOOR CLEAN OUT. MATCH EXISTING INVERT OF 1'-6".
- 2 EXISTING 4" SANITARY PIPING BELOW SLAB SHALL BE REMOVED AND REPLACED WITH NEW SANITARY PIPING. INVERT AT STREET CONNECTION SHALL MATCH EXISTING AT -7'-6"
- 3 EXISTING SANITARY RISER TO REMAIN FOR UPSTAIRS TENANT. CONNECT TO EXISTING AT BASE OF RISER.
- 4 SOLIDS INTERCEPTOR SHALL BE JRSMITH 8720-35 (OR EQUAL), WITH FINE MESH LINER AND BUCKET CHAINED TO COVER. COORDINATE ELEVATION OF INLET AND OUTLET TO FIT PIPING.
- 5 3" HUB DRAIN WITH 8" TALL, 8" Ø FUNNEL. TOP OF FUNNEL SHALL BE 16" AFF.
- 6 2" VENT UP ON INSIDE FACE OF EXISTING DEMISING WALL. ROUTE VENT AT 11'-0" AFF.
- 7 2" VENT OUT EXTERIOR WALL. TURN VENT UP AND TERMINATE MIN. OF 12'-0" ABOVE GRADE.
- 8 INSTALL AIR ADMITTANCE VALVE ON TOP OF SANITARY RISER FROM FIXTURE. SET VALVE 10'-0" AFF IN ACCESSIBLE LOCATION.

1  
P-1  
SCALE: 1/4" = 1'-0"

**FLOOR PLAN - SANITARY, WASTE, AND VENT**